

# GEOMETRIEN BIKE

	A	B	C	D	E	F	G	H	REACH	STACK
GRÖSSE	SITZROHR	OBERROHRLÄNGE HORIZONTAL	STEUERROHR	LENKWINKEL	SITZWINKEL	KETTENSTREBE	RADSTAND	TRETLAGERHÖHE		
<b>AMBER RSC, S</b> <span style="float: right;">*Grösse L nur beim Amber RSC</span>										
S	432	571	110	67.6°	74.1°	445	1139	3	402	595
M	483	596	120				1165		424	605
L*	533	616	130				1186		442	614
<b>SPHEN RSC, RS, S, PRO, COMP, ELITE</b> <span style="float: right;">*Grösse XS nur beim SPHEN Pro</span>										
XS*	390	566	90	68.5°	74.5°	433	1109	-37	398	604
S	420	584	95	69°			1123		415	611
M	460	603	100				1142		432	616
L	500	621	105				1161		449	620
<b>SPHEN PRO+</b>										
S	420	584	104	68.7°	74.5°	445	1141	-31	415	611
M	460	603	110				1160		432	616
L	500	621	114				1178		449	620
<b>MORION RS, S 29"</b>										
S	430	560	95	69.2°	74.5° 68.5°	438	1097	-45	395	595
M	465	588	105				1125		420	605
L	500	613	115				1152		443	614
<b>MORION S, COMP 27.5"</b> <span style="float: right;">*Grösse L nur beim Morion S</span>										
S	445	575	114	69.5°	74.5°	435	1106	-20	411	589
M	485	600	128				1133		433	602
L*	515	625	142				1159		454	615
<b>MORION PRO 27.5"</b>										
S	445	575	114	69.5°	74.5°	435	1106	-20	411	589
M	485	600	128				1133		433	602
L	515	625	142				1159		454	615
XL	545	635	158				1170		460	630
<b>MORION ELITE 27.5"</b>										
XS	415	550	100	69.5°	74.5°	435	1080	-20	390	576
S	445	575	114				1106		411	589
M	485	600	128				1133		433	602
L	515	625	142				1159		454	615
<b>BERYLL RSC, RS, S</b>										
S	430	590	100	71°	73°	438	1078	-65	399	624
M	465	615	110				1104		421	633
L	500	635	120				1124		438	643
<b>BERYLL SC</b>										
XS	381	565	100	70.5°	73.5°	425	1052	-45	391	587
S	432	585	107		73°		1062		403	597
M	483	595	117		1072		410		605	
<b>BERYLL PRO</b>										
XS	381	555	95	70.5°	73.5°	435	1047	-53	379	594
S	432	570	110				1063		390	609
M	483	585	120				1078		402	618
L	533	600	130				1094		414	627
XL	584	615	140				1109		426	637
<b>BERYLL COMP</b>										
XS	381	555	95	70.5°	73.5°	435	1047	-53	379	594
S	432	570	110				1063		390	609
M	483	585	120				1078		402	618
L	533	600	130				1094		414	627
<b>BERYLL ELITE</b>										
XS	381	555	95	70.5°	73.5°	435	1047	-53	379	594
S	432	570	110				1063		390	609
M	483	585	120				1078		402	618
<b>SAPHIR SC, PRO, COMP</b>										
XS	415	550	100	69.5°	74.5°	435	1080	-20	390	576
S	445	575	114				1106		411	589

# GEOMETRIEN E-BIKE

	A	B	C	D	E	F	G	H	REACH	STACK
GRÖSSE	SITZROHR	OBERROHRLÄNGE HORIZONTAL	STEUERROHR	LENKWINKEL	SITZWINKEL	KETTENSTREBE	RADSTAND	TRETLAGERHÖHE		
<b>E.T. (ALLE MODELLE)</b>									*Grösse L nur beim Herrenmodell	
S	470	555	142	67°	73°	485	1138	-65	357	646
M	500	580	157				1165		378	660
L*	550	605	172				1191		399	674
<b>ETERRA COMP M</b>										
M	460	574	160	69°	73°	465	1108	-60	383	624
L	510	594					1129		403	624
<b>ETERRA COMP L, COMP T, ELITE L</b>										
S	460	574	160	69°	73°	465	1088	-60	363	624
M	510	594					1108		383	624
<b>ESPHEN PRO, EVO, COMP</b>										
S	410	565	120	68°	73°	465	1131	-14	381	602
M	440	580	120				1146		396	602
L	470	595	130				1162		408	611
<b>EBERYLL COMP, ELITE</b>										
S	400	570	120	70°	73°	455	1087	-51	382	616
M	450	585	130				1103		394	625
L	500	600	140				1118		406	635

